

Mercury 175 HP Pro XS

\$34,548.00



Description

The 175hp Pro XS provides hard-charging performance to put you out front and keep you there. Pro XS is the choice of tournament anglers and performance enthusiasts who don't like coming second. The Mercury V-6 Pro XS transforms every drop of fuel into performance delivering class leading fuel economy at cruising speed and wide-open throttle. Advanced Range Optimisation (ARO) utilises closed-loop fuel control to precisely adjust the fuel mixture and deliver the best possible efficiency. All Pro XS FourStroke models now come with a 3+3=6 Year factory warranty. ENGINE DETAILS

Engineers packed incredible power into this lightweight and compact outboard. Great for bass and multi-species fishing boats. SPECIFICATIONS - 175

HP / kW	175 / 130
Engine type	V-6
MidSection	Conventional MidSection
Displacement (CID/CC)	209
Displacement (L)	3.4
Cylinder Configuration	V-6 [64 degree] with Dual Overhead Cam [DOHC] and 24-valves
Full throttle RPM	5400-6000
Air induction	Performance-Tuned Long-Runner Intake Manifold
Fuel induction system	Electronic Fuel Injection (EFI) Computer Controlled with Advanced Range Optimization
Alternator amp / Watt	85-amp (1071 Watt) with Idle Charge
Recommended fuel	Unleaded Regular 87 Octane Minimum (R+M/2) or 90 RON 10% Ethanol Maximum
Recommended oil	NMMA Certified FCW SAE 10W-30
Engine protection operator warning system	SmartCraft Engine Guardian



Compatible with SmartCraft digital technology Yes
Starting Electric Start with SmartStart Protection
Controls Remote Mechanical
Steering Big Tiller (optional) Hydraulic (standard) Power (optional)
Shaft length 20" / 508 mm 25" / 635 mm
Gearcase ratio 1.85:1
Dry weight *Lightest model available 470 lbs / 213 kgs
CARB star rating 3
Bore and stroke 3.6 in x 3.4 in / 92 mm x 86 mm
Ignition SmartCraft PCM 112 Digital Inductive
Cooling system Water-cooled with thermostat
Gear shift F-N-R
Gearcase options 4.8"
Trim system Power trim and tilt
Exhaust system Through prop
Color Phantom Black
Lubrication system Integrated wet sump
Oil Capacity 7.0 Quarts / 6.6 Liters
Maximum Trim Range 20° (-6° to 14°)
Maximum Tilt Range 73° (-6° to 67°)

