

Mercury 225 HP Sea Pro

\$43,435.00



Description

The new Mercury V-8 SeaPro outboard models bring more of everything to the job—more displacement, more power, more efficiency and more durability. The impressive muscle of our new V-8 4.6-litre powerhead is specifically designed for commercial duty and delivers our best-ever fuel economy and FourStroke performance. The combination of ample torque and low weight makes these engines ideal for heavily-loaded boats.

Guaranteed to do its job, so you can do yours. Mercury SeaPro FourStroke models come with a 2+1 = 3 year commercial factory warranty. ENGINE DETAILS

Mercury engineers strategically trimmed weight to produce some of the lightest engines in the class—by up to 30 pounds—and the powerhead configuration has been optimized to minimize size. Ideal for commercial fishing vessels, commercial workboats and law-enforcement boats.

SPECIFICATIONS - 225

HP / kW	225/168
Engine type	V-8
MidSection	Conventional MidSection
Displacement (CID/CC)	279 CID
Displacement (L)	4.6L
Cylinder Configuration	V-8 [64 degree] with Dual Overhead Cam [DOHC] and 32-valves
Full throttle RPM	4800-5600
Air induction	Performance-Tuned Long-Runner Intake Manifold
Fuel induction system	Electronic Fuel Injection (EFI) Computer Controlled with Advanced Range Optimization
Alternator amp / Watt	85-amp (1071 Watt) with Idle Charge
Recommended fuel	Unleaded Regular 87 Octane Minimum (R+M/2) or 90 RON 10% Ethanol Maximum
Recommended oil	NMMA Certified FCW SAE 25W-40 (Optional 10W-30 for Cold Conditions)



Engine protection operator warning system SmartCraft Engine Guardian
Compatible with SmartCraft digital technology Yes
Starting Electric Start with SmartStart Protection
Controls Remote Mechanical or Digital Throttle & Shift (DTS)
Steering Big Tiller (optional) Hydraulic (standard) Power (optional)
Shaft length 20" / 508 mm 25" / 635 mm 30" / 762 mm
Gearcase ratio 1.75:1
Dry weight *Lightest model available 527 lbs / 239 kgs
CARB star rating 3
Bore and stroke 3.6 in x 3.4 in / 92 mm x 86 mm
Ignition SmartCraft PCM 112 Digital Inductive
Cooling system Water-cooled with thermostat
Gear shift F-N-R
Gearcase options 5.44"
Trim system Power trim and tilt
Exhaust system Through prop
Counter Rotation Available
Color Phantom Black
Lubrication system Integrated wet sump
Oil Capacity 7.0 Quarts / 6.6 Liters
Maximum Trim Range 20° (-6° to 14°)
Maximum Tilt Range 73° (-6° to 67°)

