

Mercury 250 HP Pro XS

\$48,211



Description

The 250hp Pro XS provides hard-charging performance to put you out front and keep you there. Pro XS is the choice of tournament anglers and performance enthusiasts who don't like coming second. Mercury V-8 Pro XS models transform every drop of fuel into performance delivering class leading fuel economy at cruising speed and wide-open throttle. Advanced Range Optimisation (ARO) utilises closed-loop fuel control to precisely adjust the fuel mixture and deliver the best possible efficiency. All Pro XS FourStroke models now come with a 3+3=6 Year factory warranty. ENGINE DETAILS

Great for bass and multi-species fishing boats. SPECIFICATIONS - 250

HP / kW	250 / 186
Engine type	V-8
MidSection	Conventional MidSection
Displacement (CID/CC)	279 CID
Displacement (L)	4.6L
Cylinder Configuration	V-8 [64 degree] with Dual Overhead Cam [DOHC] and 32-valves
Full throttle RPM	5600-6200
Air induction	Performance-Tuned Long-Runner Intake Manifold
Fuel induction system	Electronic Fuel Injection (EFI) Computer Controlled with Advanced Range Optimization
Alternator amp / Watt	85-amp (1071 Watt) with Idle Charge
Recommended fuel	Unleaded Regular 87 Octane Minimum (R+M/2) or 90 RON 10% Ethanol Maximum
Recommended oil	NMMA Certified FCW SAE 10W-30
Engine protection operator warning system	SmartCraft Engine Guardian
Compatible with SmartCraft digital technology	Yes



Starting Electric Start with SmartStart Protection
Controls Remote Mechanical or Digital Throttle & Shift (DTS)
Steering Big Tiller (optional) Hydraulic (standard) Power (optional)
Shaft length 20" / 508 mm 25" / 635 mm
Gearcase ratio 1.75:1
Dry weight *Lightest model available 505 lbs / 229 kgs
CARB star rating 3
Bore and stroke 3.6 in x 3.4 in / 92 mm x 86 mm
Ignition SmartCraft PCM 112 Digital Inductive
Cooling system Water-cooled with thermostat
Gear shift F-N-R
Gearcase options 20": TorqueMaster 25": 5.44"
Trim system Power trim and tilt
Exhaust system Through prop
Color Phantom Black
Lubrication system Integrated wet sump
Oil Capacity 7.0 Quarts / 6.6 Liters
Maximum Trim Range 20° (-6° to 14°)
Maximum Tilt Range 73° (-6° to 67°)

