

Mercury MerCruiser 4.5L 200HP

POA



Description

The Next Generation featuring a host of engineering innovations, the 4.5L series establishes new standards for power-to-weight ratio, driver experience, acceleration, durability, and ease of maintenance.

HP / kW	200 / 149
Maximum RPM (WOT)	4400 - 4800
Engine type	V6, 2-valve/cylinder pushrod
Displacement (L)	4.5
Bore and stroke	4.0 x 3.6" / 102 x 92 mm
Fuel requirement	Unleaded 91 RON Minimum
Fuel delivery system	Computer controlled Multi-Port Electronic Fuel Injection (MPI)
Air induction	Performance-Tuned Scroll Intake Manifold
Ignition	SmartCraft PCM 112 Digital Inductive
Alternator amp / Watt	70 amp / 882 watt (Belt-Driven)
Water drain system	Easy Drain "Season Extender"
Exhaust system	Through prop
Cooling system	Water cooled with thermostat; FWC available as factory option
Lubrication system	Integrated wet sump
Recommended oil	NMMA Certified FCW 25W-40 Synthetic Blend



Engine guardian system
Dimensions (L x W x H) 28 x 30 x 22" / 696 x 740 x 559 mm
Weight (engine only) 756 lbs / 343 kg
Compatible drives Alpha

