

Suzuki 115HP 4 Stroke

\$19,532



Description

Suzuki Repower with Suzuki

MODEL DF115B

RECOMMENDED TRANSOM HEIGHT mm (in.) L: 508, X: 635

STARTING SYSTEM Electric

WEIGHT kg *1 L: 188, X: 192

ENGINE TYPE DOHC 16-Valve

FUEL DELIVERY SYSTEM Multi-Point Sequential Electronic Fuel Injection

NO. OF CYLINDERS 4

PISTON DISPLACEMENT cm3 (cu.in.) 2,045

BORE Å— STROKE mm (in.) 86 x 88

MAXIMUM OUTPUT kW (PS) 84.6

FULL THROTTLE OPERATING RANGE rpm 5,000-6,000

STEERING Remote

OIL PAN CAPACITY Lit. 5.5

IGNITION SYSTEM Fully-transistorized

ALTERNATOR 12V 40A

ENGINE MOUNTING Shear Mount

TRIM METHOD Power Trim and Tilt

GEAR RATIO 2.59:1

GEAR SHIFT F-N-R

Phone: (09) 271 1575

Email: sales@aucklandmarine.co.nz

Website: <https://www.aucklandmarine.co.nz/>

321 Ti Rakau Drive Burswood, Auckland 2013 NZ



EXHAUST Through Prop Hub Exhaust

PROPELLER SELECTION (Pitch)*2 All propellers are the 3-blade type 15-25

