

# Suzuki 150HP 4 Stroke

\$21,440



## Description

Suzuki Repower with Suzuki

MODEL DF150A

RECOMMENDED TRANSOM HEIGHT mm (in.) L:508 (20), X:635 (25)

STARTING SYSTEM Electric

WEIGHT kg \*1 L:235, X:240

ENGINE TYPE DOHC 16-Valve

FUEL DELIVERY SYSTEM Multi-Point Sequential Electronic Fuel Injection

NO. OF CYLINDERS In-Line 4

PISTON DISPLACEMENT cm<sup>3</sup> (cu.in.) 2,867 (174.9)

BORE Å— STROKE mm (in.) 97 Å— 97 (3.81Å— 3.81)

MAXIMUM OUTPUT kW (PS) 110.0 (150)

FULL THROTTLE OPERATING RANGE rpm 5,000-6,000

STEERING Remote

OIL PAN CAPACITY Lit. (U.S. qt) 8.0 (8.5)

IGNITION SYSTEM Fully-transistorized

ALTERNATOR 12V 44A

ENGINE MOUNTING Shear Mount

TRIM METHOD Power Trim and Tilt

GEAR RATIO 2.50:1

GEAR SHIFT F-N-R

---

Phone: (09) 271 1575

Email: [sales@aucklandmarine.co.nz](mailto:sales@aucklandmarine.co.nz)

Website: <https://www.aucklandmarine.co.nz/>

321 Ti Rakau Drive Burswood, Auckland 2013 NZ



EXHAUST Through Prop Hub Exhaust

PROPELLER SELECTION (Pitch) \*2

3 blades and 4 blades propeller are available. 15"-27.5"(R/R), 17"-26(C/R)

