

Suzuki 175HP 4 Stroke

\$24,581



Description

Suzuki Repower with Suzuki

MODEL DF175A

RECOMMENDED TRANSOM HEIGHT mm (in.) L:508 (20), X:635 (25)

STARTING SYSTEM Electric

WEIGHT kg *1 L:235, X:240

ENGINE TYPE DOHC 16-Valve

FUEL DELIVERY SYSTEM Multi-Point Sequential Electronic Fuel Injection

NO. OF CYLINDERS In-Line 4

PISTON DISPLACEMENT cm³ (cu.in.) 2,867 (174.9)

BORE Å— STROKE mm (in.) 97 Å— 97 (3.81Å— 3 .81)

MAXIMUM OUTPUT kW (PS) 129.0 (175)

FULL THROTTLE OPERATING RANGE rpm 5,500-6,100

STEERING Remote

OIL PAN CAPACITY Lit. (U.S. qt) 8.0 (8.5)

IGNITION SYSTEM Fully-transistorized

ALTERNATOR 12V 44A

ENGINE MOUNTING Shear Mount

TRIM METHOD Power Trim and Tilt

GEAR RATIO 2.50:1

Phone: (09) 271 1575

Email: sales@aucklandmarine.co.nz

Website: <https://www.aucklandmarine.co.nz/>

321 Ti Rakau Drive Burswood, Auckland 2013 NZ



GEAR SHIFT F-N-R

EXHAUST Through Prop Hub Exhaust

PLEASE NOTE: Price quoted does not include gauges, remotes and rigging kit. Please talk with our freindly sales staff.

