Suzuki 300HP 4 Stroke \$38,815



Description

Suzuki Repower with Suzuki DF300HP THIS PROMOTION WILL BE FOR A LIMITED TIME. MODEL DF300AP **** RECOMMENDED TRANSOM HEIGHT mm X:635, XX:762 STARTING SYSTEM Electric WEIGHT (KG) ** X: 290, XX: 299 ENGINE TYPE DOHC 24-Valve FUEL DELIVERY SYSTEM Mutli-Point Sequential Electronic Fuel Injection NO. OF CYLINDERS V6 (55-degree) PISTON DISPLACEMENT (cm3) 4,028 BORE X STROKE (mm) 98 x 89 MAXIMUM OUTPUT (kW) 220.7 FULL THROTTLE OPERATING RANGE (rpm) 5,700-6,300 STEERING Remote OIL PAN CAPACITY (Lit.) 8 IGNITION SYSTEM Fully-transistorized ALTERNATOR 12V 54A ENGINE MOUNTING Shear Mount TRIM METHOD Power Trim and Tilt



GEAR RATIO 2.08:1 GEAR SHAFT F-N-R (Drive-by-wire) EXHAUST Through Prop-Hub Exhaust

PLEASE NOTE: Price quoted does not include gauges, remotes and rigging kit. Please talk with our freindly sales staff.

